In The Claims

Please amend the claims as follows:

1-18. (cancelled)

19. (currently amended) Apparatus for storing and transporting piece good articles in U-

shaped pockets having a flexible bottom and flexible lateral limb sidewalls which articles tend to

distort the sidewalls and a transverse wall connecting internal surfaces of said pockets, the

sidewalls being suspended in a support frame in the proximity of an upper edge of the pockets

and wherein an at least one attachment exterior to the pockets is provided for stabilizing a lower

end of the pockets.

20. (currently amended) Apparatus according to claim 19 wherein the attachment is

mounted to the pockets (4, 5) in the proximity of and below a lateral loading opening (14).

21. (previously amended) Apparatus for storing and transporting piece good articles in U-

shaped pockets having a flexible bottom and flexible lateral limb sidewalls which articles tend to

distort the sidewalls and a transverse wall connecting internal surfaces of said pockets, the

sidewalls being suspended in a support frame in the proximity of an upper edge of the pockets

and wherein an attachment is provided for stabilizing a lower end of the pockets, wherein the

attachment is mounted to the pockets (4, 5) in the proximity of a lateral loading opening (14) and

wherein the attachment is in the proximity of two lower ends of a U-shaped pocket (4, 5).

Date: April 26, 2004

22. (cancelled)

23. (previously amended) Apparatus according to claims 21 wherein the attachment includes

means for providing a tensioning force upon the sidewalls.

24. (original) Apparatus according to claim 23 wherein the means for providing a tensioning

force comprises a weight hanging on the pocket (4, 5).

25. (original) Apparatus according to claim 23 wherein the means for providing a tensioning

force comprises elastic pulling downwardly on the pocket.

26. (previously amended) Apparatus according to claim 21 further comprising openings (9)

in the lateral limb sidewalls (11, 12) below the bottom and a bar (6) extending transversely

through the sidewalls, wherein the weight of the bar provides a downwardly directed tensioning

force upon the sidewalls (11, 12) of the pockets (4, 5).

27. (withdrawn) Apparatus according to claim 26 wherein ends of the bar (6) are

accommodated in substantially vertically extending guides (7).

Date: April 26, 2004

28. (original) Apparatus according to claim 26 wherein the bar (6) is biased away from the

bottom wall by elastic pulling downwardly on the bar.

29. (withdrawn) Apparatus according to claim 27 wherein the guides (7) for the bar ends (6)

have a securing means to prevent the bar ends from unintentionally sliding out of the guide.

30. (original) Apparatus according to claim 19 wherein a transverse portion (21) extends

between the sidewalls.

31. (original) Apparatus according to claim 19 wherein the transverse portion (21) is elastic.

32. (previously amended) Apparatus according to claim 21 wherein at least one holding

element (22) is provided on a sidewall (11, 12) in an interior of the pocket.

33. (previously amended) Apparatus for storing and transporting piece good articles in U-

shaped pockets having a flexible bottom and flexible lateral limb sidewalls which articles tend to

distort the sidewalls and a transverse wall connecting internal surfaces of said pockets, the

sidewalls being suspended in a support frame in the proximity of an upper edge of the pockets

and wherein an attachment is provided for stabilizing a lower end of the pockets, wherein a

transverse portion (21) extends between the sidewalls, and wherein at least one holding element

(22) is provided on a sidewall (11, 12) in an interior of the pocket.

34. (original) Apparatus according to claim 33 wherein an end of the transverse portion (21) is

connected to the holding element (22).

35. (original) Apparatus according to claim 34 wherein on both sidewalls in the interior of the

pockets (4, 5) is a holding element (22) extending substantially in the transverse portion (21)

extending between said holding elements (22).

36. (original) Apparatus according to claim 35 wherein the holding elements (22) and the

transverse portion (21) substantially define an H-shape, wherein ends of limbs of the H-shape are

respectively secured to a sidewall (11, 12) of the pocket (4, 5).

37. (original) Apparatus according to claim 35 wherein the holding elements (22) and the

transverse portion (13) are made in one piece from elastic material.

38. (previously amended) Apparatus for storing and transporting piece good articles in U-

shaped pockets having a flexible bottom and flexible lateral limb sidewalls which articles tend to

distort the sidewalls and a transverse wall connecting internal surfaces of said pockets, the

sidewalls being suspended in a support frame in the proximity of an upper edge of the pockets

and wherein an attachment is provided for stabilizing a lower end of the pockets and wherein

elastic holding elements are mounted to a lower edge of the U-shaped pockets in such a way that

Attorney Docket No. WSP201US U.S. Patent Application No. .09/937,475

Date: April 26, 2004

upon downward movement of upper frame portions holding the pockets, the elastic holding elements prevent the pockets from moving out of the frame.